



Qty: 4 Ref: 2702 Start of temporary diversion route	
Qty: 3 Ref: 2702 End of temporary diversion route	
Qty: 9 Ref: 2703 Direction of temporary diversion route from junction ahead	
Qty: 3 Ref: 2703 Direction of temporary diversion route from junction ahead	
Qty: 1 Ref: 2703 Direction of temporary diversion route from junction ahead	
Qty: 3 Ref: 2703 Direction of temporary diversion route from junction ahead	
Qty: 4 Ref: 2704 Direction of temporary diversion route	
Qty: 5 Ref: 2704 Direction of temporary diversion route	

VolkerHighways

SAFETY ZONE DIMENSIONS
 Permanent speed limit 40mph
 Sideways safety zone 0.5m
 Longways safety zone 15m
 (Dimensions are minima)

Drawing Office			
DWG Number	VH5216		Customer
Revision	0	Date Surveyed	10/06/22
Drawn By	RQ	Date Drawn	10/06/22
Survey By	Cust	Phase Number	1 of 1
Checked By	PT	Page Number	1 of 6

- 750mm Road Signs
- Variable Message Sign

Site Details Address

**Twinch Lane,
Slough,
SL1 5AL**

Diversion

- Drawing Notes**
1. Do not scale from this drawing, all dimensions to be verified on site.
 2. It will be the responsibility of the contractor to ensure that all temporary traffic management shall be in accordance with the Traffic Signs Manual chapter 8 2009, Safety at Street works 2013, Traffic Signs Regulations and General Directions 2016 and all current / relevant Health and safety legislation.
 3. All signage placement will be subject to available safe working space and all signage will be secured / ballasted with straps or sandbags.
 4. A minimum lateral safety zone of 0.5m will be maintained at all times.
 5. A minimum running lane of 3.0m will be maintained for vehicles.
 6. A safe segregated working area will be provided and maintained at all times.
 7. Minimum size of temporary signage will be 750mm.