



Notes:

- Nearside Signing only subject to RA.
- Alternative taper cone spacing will be at 9m



Contract No	133-S018275	Client: OPENREACH
Date	19/01/2024	Site Location / Drawing Title
Drawn by	GB (864)	NEAR 13A AND RED LION, ST MARY'S ROAD, LANGLEY, SLOUGH SL3 7EN
Approved By	xxxxxxxxxx	
Purpose of works	civil works	
Version Number	000	
Amended By	xxxxxxxxxx	
Amendment Date	xx/xx/xxxx	Scale
Sheet No	2 of 2	OS Licence No
		NOT TO SCALE
		000000000000

DETAIL A (A)
 Prescribed sign to Diagram 610 above and behind cones
 Running lane(s)
 Hand
 Shoulder
 Three only close spaced 750mm or 1m high traffic cones
 45°
 Notes:
 1) During darkness, a single warning light to BS EN 12352:2006 should be provided.
 2) Traffic cones should conform to diagram 7101.1 and to BS EN 13422.

DETAIL B (B)
 Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
 Single/Dual carriageway 50mph or more - 750mm traffic cones, spacing 1.5m.
 Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.
 Notes:
 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 2) 45° tapers have 1.2m spacing, no relaxations.
 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

DETAIL C1 (C1)
 Single/Dual carriageway 40mph or less - 450mm traffic cones.
 Single/Dual carriageway 50mph or more - 750mm traffic cones.
 Notes:
 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 2) For relaxation to Detail C1 see Table A1.3 (Appendix 1).

DETAIL C2 (C2)
 Single carriageway 40mph or less - 450mm traffic cones.
 Single/Dual carriageway 50mph or more - 750mm traffic cones.
 Notes:
 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3.

DETAIL D (D)
 Single/Dual carriageway 40mph or less - 450mm traffic cones.
 Single/Dual carriageway 50mph or more - 750mm traffic cones.
 Notes:
 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
 2) Detail D applies only to relaxation cases.

DETAIL AL (AL)
 Manned Airlock system.
 Notes:
 1) Minimal site traffic 25 - 30m air lock is sufficient. Extend airlock for larger work vehicle flow.
 2) Red lamps to be used on Nissen Barrier (all HE networks)

THIS DOCUMENT IS UNCONTROLLED WHEN PRINTED
 The electronic version of this document is the approved and most current. Any printed version is uncontrolled and may not be current.

SUNBELT RENTALS
 Sunbelt Rentals UK (Traffic Management)
 Kemble Airfield Enterprise Park, Cirencester Road,
 Kemble GL7 6BQ
 Telephone: 0370 050 0792